


GENERAL DESCRIPTION

This N-Channel enhancement mode field effect transistor is produced using high cell density, DMOS technology. These products have been designed to minimize on-state resistance while providing rugged, reliable, and fast switching performance. It can be used in most applications requiring up to 115mA DC and can deliver pulsed currents up to 800mA. This product is particularly suited for low voltage, low current applications such as small servo motor control, power MOSFET gate drivers, and other switching applications.

PIN CONFIGURATION


SOT-23
Top View



FEATURES

- ◆ High Density Cell Design for Low $R_{DS(ON)}$
- ◆ Voltage Controlled Small Signal Switch
- ◆ Rugged and Reliable
- ◆ High Saturation Current Capability

SYMBOL



N-Channel MOSFET

ORDERING INFORMATION

Part Number	Package
CMT2N7002	SOT-23

ABSOLUTE MAXIMUM RATINGS

Rating	Symbol	Value	Unit
Drain Source Voltage	V_{DSS}	60	V
Drain-Gate Voltage ($R_{GS} = 1.0M\Omega$)	V_{DGR}	60	V
Drain to Current — Continuous	I_D	± 115	mA
— Pulsed	I_{DM}	± 800	
Gate-to-Source Voltage — Continue	V_{GS}	± 20	V
— Non-repetitive	V_{GSM}	± 40	V
Total Power Dissipation	P_D	225	mW
Derate above 25°C		1.8	$mW/^\circ C$
Single Pulse Drain-to-Source Avalanche Energy — $T_J = 25^\circ C$ ($V_{DD} = 50V$, $V_{GS} = 10V$, $I_{AS} = 0.8A$, $L = 30mH$, $R_G = 25\Omega$)	E_{AS}	9.6	mJ
Operating and Storage Temperature Range	T_J , T_{STG}	-55 to 150	°C
Thermal Resistance — Junction to Ambient	θ_{JA}	417	°C/W
Maximum Lead Temperature for Soldering Purposes, 1/8" from case for 10 seconds	T_L	300	°C

ELECTRICAL CHARACTERISTICS

Unless otherwise specified, $T_J = 25^\circ\text{C}$.

Characteristic	Symbol	CMT2N7002			Units
		Min	Typ	Max	
Drain-Source Breakdown Voltage ($V_{GS} = 0 \text{ V}$, $I_D = 10 \mu\text{A}$)	$V_{(BR)DSS}$	60			V
Drain-Source Leakage Current ($V_{DS} = 60 \text{ V}$, $V_{GS} = 0 \text{ V}$) ($V_{DS} = 60 \text{ V}$, $V_{GS} = 0 \text{ V}$, $T_J = 125^\circ\text{C}$)	I_{DSS}			1.0 0.5	μA mA
Gate-Source Leakage Current-Forward ($V_{gsf} = 20 \text{ V}$)	I_{GSSF}			100	nA
Gate-Source Leakage Current-Reverse ($V_{gsf} = -20 \text{ V}$)	I_{GSSF}			-100	nA
Gate Threshold Voltage *	$V_{GS(th)}$	1.0		2.5	V
($V_{DS} = V_{GS}$, $I_D = 250 \mu\text{A}$)					
On-State Drain Current ($V_{DS} \geq 2.0 \text{ V}_{DS(on)}$, $V_{GS} = 10\text{V}$)	$I_{d(on)}$	500			mA
Static Drain-Source On-Resistance *	$R_{DS(on)}$			7.5 13.5 7.5 13.5	Ω
($V_{GS} = 10 \text{ V}$, $I_D = 0.5\text{A}$) ($V_{GS} = 10 \text{ V}$, $I_D = 0.5\text{A}$, $T_C = 125^\circ\text{C}$) ($V_{GS} = 5.0 \text{ V}$, $I_D = 50\text{mA}$) ($V_{GS} = 5.0 \text{ V}$, $I_D = 50\text{mA}$, $T_C = 125^\circ\text{C}$)					
Drain-Source On-Voltage *	$V_{DS(on)}$			3.75 0.375	V
($V_{GS} = 10 \text{ V}$, $I_D = 0.5\text{A}$) ($V_{GS} = 5.0 \text{ V}$, $I_D = 50\text{mA}$)					
Forward Transconductance ($V_{DS} \geq 2.0 \text{ V}_{DS(on)}$, $I_D = 200\text{mA}$) *	g_{FS}	80			mmhos
Input Capacitance	C_{iss}			50	pF
Output Capacitance	C_{oss}			25	pF
Reverse Transfer Capacitance	C_{rss}			5.0	pF
Turn-On Delay Time	$t_{d(on)}$			20	ns
Turn-Off Delay Time	$t_{d(off)}$			40	ns
Diode Forward On-Voltage ($I_S = 115 \text{ mA}$, $V_{GS} = 0\text{V}$)	V_{SD}			-1.5	V
Source Current Continuous (Body Diode)	I_S			-115	mA
Source Current Pulsed	I_{SM}			-800	mA

* Pulse Test: Pulse Width $\leq 300\mu\text{s}$, Duty Cycle $\leq 2\%$

TYPICAL ELECTRICAL CHARACTERISTICS




Figure 1. Ohmic Region




Figure 2. Transfer Characteristics




Figure 3. Temperature versus Static
Drain-Source On-Resistance





Figure 4. Temperature versus Gate
Threshold Voltage



V_{DS} – Drain-to-Source Voltage (V)

Figure 5. Capacitance

PACKAGE DIMENSION

SOT-23						
SYMBOLS	DIMENSIONS IN MILLIMETERS			DIMENSIONS IN INCHES		
	MIN	NOM	MAX	MIN	NOM	MAX
A	1.05	---	1.35	0.041	---	0.053
A1	0.05	---	0.15	0.002	---	0.006
A2	1.00	1.10	1.20	0.039	0.043	0.047
b	0.25	---	0.50	0.010	---	0.020
b1	0.25	0.40	0.45	0.010	0.016	0.018
c	0.08	---	0.20	0.003	---	0.008
c1	0.08	0.11	0.15	0.003	0.004	0.006
D	2.70	2.90	3.00	0.106	0.114	0.118
E	2.20	2.40	2.60	0.087	0.094	0.102
E1	1.20	1.30	1.40	0.047	0.051	0.055
L	0.35	0.45	0.55	0.014	0.018	0.022
L1	0.60 REF			0.024 REF		
e	0.95 BSC			0.037 BSC		
e1	1.90 BSC			0.075 BSC		
θ_1	0°	5°	10°	0°	5°	10°
θ_2	3°	5°	7°	3°	5°	7°
θ_3	6°	8°	10°	6°	8°	10°



IMPORTANT NOTICE

Champion Microelectronic Corporation (CMC) reserves the right to make changes to its products or to discontinue any integrated circuit product or service without notice, and advises its customers to obtain the latest version of relevant information to verify, before placing orders, that the information being relied on is current.

A few applications using integrated circuit products may involve potential risks of death, personal injury, or severe property or environmental damage. CMC integrated circuit products are not designed, intended, authorized, or warranted to be suitable for use in life-support applications, devices or systems or other critical applications. Use of CMC products in such applications is understood to be fully at the risk of the customer. In order to minimize risks associated with the customer's applications, the customer should provide adequate design and operating safeguards.

HsinChu Headquarter

5F, No. 11, Park Avenue II,
Science-Based Industrial Park,
HsinChu City, Taiwan
TEL: +886-3-567 9979
FAX: +886-3-567 9909

Sales & Marketing

11F, No. 306-3, SEC. 1, Ta Tung Road,
Hsichih, Taipei Hsien 221, Taiwan
TEL: +886-2-8692 1591
FAX: +886-2-8692 1596