




Schottky Rectifiers

1.0 to 75 Amperes
20 to 60 Volts

IO (AMPS)	1.0		2.0	3.0
	25	25	25	25
IFSM (AMPS)	25	50	75	80
CASE	 DO-41 *		 DO-15	 DO-201AD
VRRM (VOLTS)				
20	1N5817	CRSH1-2	CRSH2-2	1N5820
30	1N5818	CRSH1-3	CRSH2-3	1N5821
40	1N5819	CRSH1-4	CRSH2-4	1N5822
50		CRSH1-5	CRSH2-5	
60		CRSH1-6		

V _F MAX @ I _F = I _O				
20V	0.45V MAX @ 1.0A	0.50V MAX @ 1.0A	0.55V MAX @ 2.0A	0.475V MAX @ 3.0A
30V	0.55V MAX @ 1.0A	0.50V MAX @ 1.0A	0.55V MAX @ 2.0A	0.500V MAX @ 3.0A
40V	0.60V MAX @ 1.0A	0.50V MAX @ 1.0A	0.55V MAX @ 2.0A	0.525V MAX @ 3.0A
50V		0.70V MAX @ 1.0A	0.55V MAX @ 2.0A	
60V		0.70V MAX @ 1.0A		

I _R MAX @ V _{RRM}	1.0mA	1.0mA	1.0mA	2.0mA
---------------------------------------	-------	-------	-------	-------

* Also available in DO-41SP Case (0.6mm lead diameter) with Radial Tape and Reel (DO-41SP-RPCU). See page 239.