

[PRODUCTS](#)
[Rocker switches](#)
[Pushbutton switches](#)
[Toggle switches](#)
[Slide switches](#)
[Rotary switches](#)
[Foot switches](#)
[Tact and key switches](#)
[Snap-action switches](#)
[Micro-signal switches](#)
[ECO switches](#)
[Sensors](#)
[Push'n'Drive](#)
[Systems and modules](#)
[Accessories](#)
[General information](#)
[Catalog request / download](#)
[PRODUCTS](#) ▶ [ROCKER SWITCHES](#)

## SERIES 1830 - SINGLE AND DOUBLE-POLE ROCKER SWITCHES - TO 20 (4) A 250 V AC

[◀ Show previous product](#)
[Show next product ▶](#)
[1834.3312](#)
[Drawing](#)
[Accessories](#)


Similar to original product

→ [Print data sheet](#)

**Product number** 1834.3312

Actuator color / printing

Black

Switching function Changeover switch (DPDT)

Number of poles 2-pole

connections Quick-connect terminal, 6.3

Mechanical life endurance 10E4

Rating IEC 16 (4) A 250 V AC 1E4

Rating North America 16 A 125 V AC 1/4 HP  
16 A 250 V AC 1/2 HP

Contact resistance (new condition) < 100 (1 A 12 V DC) mOhm

Insulation resistance (new condition) > 100 (500 V DC) MOhm

Proof tracking 250 PTI

Protection type Connection IP40

Ambient temperature -20 °C ... +105 °C

Ambient temperature -20 °C ... +55 °C

Flammability UL 94 V-2

Glow wire test temperature 850 °C

Actuators and additional actuators PA, black

Housing description PA, black

Connection surface external connection silver plated

Contact material Ag

Contact distance ≥ 3 mm

Plug force of the terminals ≤ 80 N

Approval marks CSA / UL / ENEC 05

Suitable for appliances of protection class II